

FEATURES:

- Universal Input 90~264VAC
- Efficiency at 83% Typical
- Protection: Short Circuit /Overload/Over Voltage
- Fully Encapsulated Plastic Case
- Internal Input Filter

Specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified

Part Number	Output Wattage	Output Voltage	Output Current		Ripple & Noise(note1)	Efficiency
	(W)	(V)	(mA)(min)	(mA)(max)	(mV) max	%(TYP)
GA015-S24C01	19	Vo=+24.0	0	800	150	83

Input Specifications

Parameters	Conditions		Min	Typ	Max	Units
Rated input voltage	Vo,lo nom			100-240		Vac
Voltage Range	Vo,lo nom	AC in	90		264	Vac
		DC in	120		370	Vdc
Frequency			47	50/60	63	Hz
Input Current	Vo,lo nom				0.5	A
Inrush Current	At 115Vac				10	A
	At 230Vac				20	A
Input Fuse	VDE/UL/CCC FUSE 2.5A/250V (Slow blow)					

Output Specifications


Parameters	Conditions		Min	Typ	Max	Units
Output Voltage Accuracy	Vi nom,lo nom	Vo			±2	%
Minimum Load	Vi nom		0			
Line Regulation	Io nom,Vi min...Vi max			±1		%
Load Regulation	Vi nom, Io min...Io nom	Vo		±2		%
Transient Recovery time	Vi nom,Io nom = $\longleftrightarrow$ 0.5 Io nom			1,000		uS
Protection	Overload		Above 110% rated output power			
			Protection type: Recovers automatically after fault condition is removed			
	Over Voltage		120%-150% rated output Voltage			
			Protection type: Zener diode clamp			
	Short circuit		Recovers automatically after fault condition is removed			

Note. 1. Ripple & noise is measured by using 20 MHz bandwidth, measured with a 47uf paralleled with a high-frequency 0.47uf capacitor across each output by full load.



General Specifications

Parameters	Conditions	Min	Typ	Max	Units
Switching Frequency	Vi nom,lo nom		65		KHz
Isolation Voltage	Input / Output	3KVac/ 5mA/5Secs			
Isolation Resistance	Input / Output,@500 Vdc	100			MΩ
Operating Temperature	Operating at Vi nom,lo nom	-20		+70	°C
Derating	Vi nom,lo nom+51 to 71°C			2	%/°C
Storage Temperature	Non Operational	-40		+85	°C
Relative Humidity@40°C	Vi nom,lo nom			95	% RH
Safety Standards	Design refer to EN62368-1				
EMI Conduction & Radiation	Design refer to EN55032				
EMS Immunity	Design refer to EN55024				
Dimension	L69.85x W48.01 x H23.37				
Cooling	Free air convection				

Temperature Derating Graph



Markings and dimensions



PIN	Model
1	Single
2	FG
3	ACN
4	ACL
5	-Vo
6	NO PIN
	+Vo

UNIT: mm Unless otherwise specified, all tolerances are ± 0.50

19Watt,Single Output,AC-DC Power Module Converter

1. Weight:145grams/pcs
2. outer carton unit : 72pcs/box
3. Weight: 11.5kg per carton

